


Triangular spacecraft

Abstract

A spacecraft having a triangular hull with vertical electrostatic line charges on each corner that produce a horizontal electric field parallel to the sides of the hull. This field, interacting with a plane wave emitted by antennas on the side of the hull, generates a force per volume combining both lift and propulsion.

Images (8)



Classifications

B64G1/409 Unconventional spacecraft propulsion systems

US20060145019A1

United States

[Download PDF](#)

[Find Prior Art](#)

[Similar](#)

Inventor: [John St. Clair](#)

Worldwide applications

2004 [US](#)

Application US11/017,093 events

2004-12-20 Application filed by St Clair John Q

2004-12-20 Priority to US11/017,093


2006-07-06 Publication of US20060145019A1

Status Abandoned

Info: [Patent citations \(6\)](#), [Legal events](#), [Similar documents](#), [Priority and Related Applications](#)

External links: [USPTO](#), [USPTO Assignment](#), [Espacenet](#), [Global Dossier](#), [Discuss](#)

Claims (4)

[Hide Dependent](#) 

1. A spacecraft comprised of the following components:
 - (a) a triangular hull in the form of an equilateral triangle;
 - (b) two copper plates attached on opposite vertical sides at each of the three corners of the hull (1 a) such that a sharp vertical edge is formed where they come together;
 - (c) an electrostatic generator used to charge the back two copper-cladded corners (1 b) to a high positive voltage, and the third forward copper-cladded corner to a high negative voltage;
 - (d) a horizontal slot antenna array mounted-on the sides of the hull; and
 - (e) a frequency generator, antenna and coaxial cables to drive the antenna array (1 d).
2. To create, by claims (1 a, 1 b, 1 c), an intense vertical line charge at the corners (1 b) and a horizontal electric field that that is parallel to the sides of the hull (1 a);
3. To create, by claims (1 d,1 e), an electromagnetic wave with a vertically polarized electric field traveling outward from the side of the hull (1 a); and
4. To create, by claims (2,3), an interaction of the electrostatic field (2) with the electromagnetic wave (3) such that a combined spacetime curvature pressure is generated on the hull in the upward and forward direction to produce lift and propulsion respectively.

Description

- BRIEF SUMMARY OF THE INVENTION**
- [0001] This invention is a spacecraft having a triangular hull with vertical electrostatic line charges on each corner. The line charges create a horizontal electric field that, together with a plane wave emitted by antennas on the side of the hull, generates a force per volume providing a unique combination of both lift and propulsion.
- BACKGROUND OF THE INVENTION**
- [0002] Referring to FIG. 1, the spacecraft has a hull in the shape of an equilateral triangle. A parabolic antenna (E) is centrally located in the bottom of the hull. An array of horizontal slot antennas is located along the side of the hull (A). Each back corner (F,G) has a corner conducting plate which is charged to a positive voltage +V. The forward corner (C) has a conducting plate charged to a negative voltage -V. A motion control hemisphere (D) is located on the bottom surface in each of the three corners.
- [0003] Referring to FIG. 2, two planes (A,B) intersect at the origin O at an opening angle beta. Each plane (x,y) is charged to a voltage V. The potential at point P is determined in polar coordinates (p,phi). The Laplace equation for the potential Phi in polar coordinates is given by:
- $$\frac{1}{p} \frac{\partial}{\partial p} \left(p \frac{\partial \Phi}{\partial p} \right) + \frac{1}{p^2} \frac{\partial^2 \Phi}{\partial \phi^2} = 0$$
- Using a separation of variables solution, the potential is given as the product of two functions:
- $$\Phi(p,\varphi)=R(p)\Psi(\varphi)$$
- which when substituted into the Laplace equation becomes:
- $$p R \frac{d}{d p} \left(p \frac{d R}{d p} \right) + \frac{1}{p^2} \Psi \frac{d^2 \Psi}{d \phi^2} = 0$$
- Since the two terms are separately functions of p and phi respectively, each one has to be constant with the sum of the constants equal to zero:
- $$p R \frac{d}{d p} \left(p \frac{d R}{d p} \right) = v^2 \quad \frac{1}{p^2} \Psi \frac{d^2 \Psi}{d \phi^2} = -v^2$$
- These two equations have solutions:
- $$R(p)=a p^{v+1} b p^{-v}$$
- $$\psi(\varphi)=A \cos(v \varphi)+B \sin(v \varphi)$$
- The azimuthal angle phi is restricted to a value in the range $0 \leq \varphi \leq \beta$. The boundary condition is that the potential Phi is equal to V for any radius p when phi=0 and phi=beta. This means that v has to be an integer value of pi so that the sine function is zero:
- $$\sin(v \beta) = \sin(m \pi \beta \beta) = \sin(m \pi) = 0 \quad m=1, 2, \dots$$
- which in turn means that the coefficient A of the cosine term has to be zero in the solution above. Choosing b=0 makes the general solution for the potential equal to:
- $$\Phi(p, \phi) = V + \sum_{m=1}^{\infty} a_m p^m \frac{\pi}{\beta} \sin\left(\frac{m \pi \phi}{\beta}\right)$$
- which shows that when the angle is zero, the sine is zero and the potential is V. If the angle is beta, then there is a multiple of pi such that the sine is zero again.
- [0004] Because the series involves positive powers of the radius, for small enough p, only the first term $m=1$ in the series is important. Thus around $p=0$, the potential is approximately
- $$\varphi(p,\varphi)=V+a_1 p^{1/\beta} \sin(\pi \varphi / \beta)$$
- [0005] The electric field component is the negative gradient of the potential:
- $$E_{\phi}(p, \phi) = -\frac{1}{p} \frac{\partial \Phi}{\partial \phi} = -\frac{\pi}{\beta} a_1 p^{1/\beta} \cos\left(\frac{\pi \phi}{\beta}\right)$$
- The surface charge distribution sigma at phi=0 and phi=beta is equal to the electric field perpendicular to the surface times the permittivity of space epsilon_0:
- $$\sigma(p) = \epsilon_0 E_{\phi}(p, 0) = -\epsilon_0 \frac{\pi}{\beta} a_1 p^{1/\beta} \cos\left(\frac{\pi \phi}{\beta}\right)$$
- Notice that if angle of intersection beta is less than pi, then the equation says that there is a very small radius to a positive power which means little charge density accumulation.
- [0006] Referring to FIG. 3, the value of beta, in the case of the triangular hull, is equal to 360° less 60° for a total of 300° or:
- $$\beta = 300 \text{ } 180 \text{ } \pi = 53 \text{ } \pi \text{ } \pi 53 \text{ } \pi - 1 = 1 \text{ } p^{25}$$
- which says that there is a charge density singularity to the two fifths power for small radius. Thus, the corner plates on the hull create a huge line charge density along the sharp vertical corner edge. The equation for the potential of a line charge density is given as:
- $$\Phi(x, y) = -\lambda 2 \text{ } \pi \epsilon_0 \text{ } \text{Ln}((x-x_0)^2 + (y-y_0)^2)$$
- where lambda is the charge per unit length in the vertical z-direction, and x_0 and y_0 are the location of the line charge in the xy-plane.
- [0007] Referring to FIG. 4, the triangular hull (D) is plotted together with the potential contours (A) and the electric field arrows (B) created by the three corner line charges. The line charges are perpendicular to the paper. Notice that the electric field arrows are parallel crossing the center parabolic antenna (C). The electric field is also parallel to the sides (D) of the triangle.
- [0008] Referring to FIG. 5, along the side of the triangle (A), an array (B) of horizontal slot antennas emit electromagnetic waves that have a vertically polarized electric E field (C). These traveling waves interact with the electric field (D) produced by the line charges on the corners of the triangle.
- [0009] Using differential forms mathematics, this combination of fields is represented by the Hodge star of the differential of the wedge product of the two fields. The antenna electromagnetic field is a combination of a traveling magnetic field B_w, and electric field E_w. The stationary field E created by the line charges is perpendicular to the traveling wave.
- $$*d(E \wedge (B_w + E_w \text{ } dt)) \text{ } \epsilon c = \text{force volume}$$
- where epsilon is the linear capacitance of space and c is the speed of light. Thus there is a force per volume around the hull.
- [0010] This combination of fields produces a spacetime curvature as determined by Einstein's General Theory of Relativity. The traveling electric field has an amplitude in the vertical z-direction and travels in the x-direction
- $$E_w = E_z \cos(x-t)$$
- The Faraday electromagnetic tensor contains all the electric and magnetic fields in all the {x,y,z} directions. The first row and first column contain the two electric

fields

$$F\beta\alpha = txyz \square 0Ex0Ez \cos (x-t)Ex000000Ez \cos (x-t)000 \square$$
The stress exerted on spacetime occurs in the xx,yy and zz-direction as calculated from the stress-energy tensor T of gravitational physics

$$4\pi \quad T\mu \quad \nu = F\mu \quad \alpha F\alpha\mu - 14 g\mu \quad \nu F\alpha \quad \beta F\alpha\beta$$
where g is the metric tensor for Cartesian space

$$g\alpha\beta = txyz \square -1000010000100001 \square$$
where the diagonal components are the coefficients of the elementary spacetime length ds squared

$$(ds)^2 = -(dt)^2 + (dx)^2 + (dy)^2 + (dz)^2$$
The calculation produces three stresses T^{XX},T^{YY} and T^{ZZ} in their respective {x,y,z} directions.

[0011] Referring to FIG. 6, these three stresses are plotted together as a 3D vector field animated over time in nine frames. The graphs show that there is a lift force as depicted by the vertical arrows as well as a force of propulsion as shown by the interspersed horizontal arrows. With the passage of time, these vectors exchange places with each other so that the lift becomes the propulsion and vice versa, creating a wavy stress-energy field around the hull.

SUMMARY OF THE INVENTION

[0012] This invention is a spacecraft with a triangular hull having charged flat plates on the vertical corners of the three sides. The two rear corners are charged to a potential V. The forward corner is charged to a potential -V. The 60° angle on the corner creates a line charge density singularity that produces a huge horizontal electric field pointing from the back to the front of the craft which is also parallel to the sides of the triangle. An array of horizontal slot antennas located on the sides of the triangular hull produce an electromagnetic wave with the electric field polarized in the vertical direction. This combination of fields produces a spacetime force in both the vertical and horizontal directions such that the spacecraft receives a lift force and a force of propulsion.

A BRIEF DESCRIPTION OF THE DRAWINGS

[0013] FIG. 1. Perspective view of triangular spacecraft.

[0014] FIG. 2. Drawing of the intersection of two charged plates in order to calculate the charge density in the corner.

[0015] FIG. 3. Perspective view of the corner angle β for the equilateral triangle.

[0016] FIG. 4. Planar 2D graph showing the electric field produced by three line charges on the corners of the triangular hull.

[0017] FIG. 5. Perspective view of electric field produced by the linear charge interacting with the traveling electromagnetic wave produced by the slot antenna.

[0018] FIG. 6. 3D vector animation of the lift and thrust force generated by the fields.

[0019] FIG. 7. Perspective view of slot antenna.

DETAILED DESCRIPTION OF THE INVENTION

[0020] Referring to FIG. 7, the antenna (A) is made out of sheet copper in which a rectangular horizontal slot (B) has been notched out using a die press and sheet metal fixture. A coaxial cable from the amplifier and frequency generator is attached across the slot by soldering the outer cable (D) to one side of the slot and the inner cable (E) to the other side of the slot. This creates the positive and negative charges across the gap which forms the vertical electric field (F) which radiates out perpendicularly to the copper sheet.

[0021] Although the invention has been described with reference to specific embodiments, such as a particular antenna system, those skilled in the art will appreciate that many modifications and variations are possible without departing from the teachings of the invention. All such modifications and variations are intended to be encompassed within the scope of the following claims.

Patent Citations (6)

Publication number	Priority date	Publication date	Assignee	Title
US3675879A *	1969-09-02	1972-07-11	Harry B Fuchs	Method and means for creating artificial gravity in spacecraft
US5269482A *	1991-09-30	1993-12-14	Shearing Ernest J	Protective enclosure apparatus for magnetic propulsion space vehicle
US20030209637A1 *	2002-05-09	2003-11-13	St. Clair John Quincy	Rotating electrostatic propulsion system
US20030209635A1 *	2002-05-09	2003-11-13	St. Clair John Quincy	Electric dipole moment propulsion system
US6974110B2 *	1999-12-07	2005-12-13	Peter Grandics	Method and apparatus for converting electrostatic potential energy
US20060038081A1 *	2004-08-04	2006-02-23	St Clair John Q	Electric dipole spacecraft
Family To Family Citations				
* Cited by examiner, † Cited by third party				

Similar Documents

Publication	Publication Date	Title
Shafranov	2012	Reviews of Plasma Physics
Bulanov et al.	2013	Relativistic mirrors in plasmas. Novel results and perspectives
Fulton et al.	1960	Classical radiation from a uniformly accelerated charge
Li	1993	Multilayer modal method for diffraction gratings of arbitrary profile, depth, and permittivity
Williams	2005	Filling the THz gap—high power sources and applications
Southwood et al.	1983	Theory of hydromagnetic waves in the magnetosphere
Kazimura et al.	1998	Generation of a small-scale quasi-static magnetic field and fast particles during the collision of electron-positron plasma clouds
Nayeri et al.	2013	Design of single-feed reflectarray antennas with asymmetric multiple beams using the particle swarm optimization method
US9928929B2	2018-03-27	Apparatus for generating focused electromagnetic radiation
Georgakopoulos et al.	2001	HIRF penetration through apertures: FDTD versus measurements
Opat et al.	1992	Electric and magnetic mirrors and gratings for slowly moving neutral atoms and molecules
Pak et al.	1995	Backscattering enhancement of electromagnetic waves from two-dimensional perfectly conducting random rough surfaces based on Monte Carlo simulations
Klewer et al.	1974	Theory of dynamical properties of dielectric surfaces
Cawthorne	2006	Polarization of synchrotron radiation from conical shock waves
Kintner et al.	1985	The status of observations and theory of high latitude ionospheric and magnetospheric plasma turbulence
Landecker	1952	Possibility of frequency multiplication and wave amplification by means of some relativistic effects
de Abajo	1999	Interaction of radiation and fast electrons with clusters of dielectrics: a multiple scattering approach
Grishchuk	1988	Gravitational-wave astronomy
Ludwig	1971	Near-field far-field transformations using spherical-wave expansions
Akhmediev	1998	Spatial solitons in Kerr and Kerr-like media
Grishchuk	1977	Gravitational waves in the cosmos and the laboratory
Fuchs et al.	1996	Acceleration of electrons in the vicinity of a lower hybrid waveguide array
Boguslawski et al.	2011	Nondiffracting kagome lattice
US20050109879A1	2005-05-26	Method and apparatus for quantum vortex implosion propulsion and species
Pathak et al.	2013	The uniform geometrical theory of diffraction and some of its applications

Priority And Related Applications

Priority Applications (1)

Application	Priority date	Filing date	Title
US11/017,093	2004-12-20	2004-12-20	Triangular spacecraft

Application	Filing date	Title
US11/017,093	2004-12-20	Triangular spacecraft

Legal Events

▲

Date	Code	Title	Description
2006-11-13	STCB	Information on status: application discontinuation	Free format text: ABANDONED -- FAILURE TO RESPOND TO AN OFFICE ACTION

Concepts

▲

machine-extracted

[Download](#)

Filter table ▼

Name	Image	Sections	Count	Query match
<div><div>■</div>copper</div>	<div>Cu</div>	claims,description	3	0.000
<div><div>■</div>copper</div>		claims,description	3	0.000
<div><div>■</div>copper</div>		claims,description	3	0.000
<div><div>■</div>interaction</div>		claims	1	0.000

[Show all concepts from the description section](#)

Data provided by IFI CLAIMS Patent Services